

TR-2015C TR-2015C Induction Pneumatic Wire Stripping Machine - Product Specifications

Stripping-length	1-20mm
Wire-diameter-range	AWG32-AWG14 (0.03-2mm2)
Working-air-pressure	0.5-0.7MPa
Dimensions-&-weight	265x70x135mm, 2kg
Equipment-name	TR-2015C Induction Pneumatic Wire Stripping Machine
Size-&-weight	265x70x135mm?2kg
Output	1800~2000 pcs/H
Wire-diameter	AWG32-AWG14(0.03-2mm2)
Adjustment-precision	0.05mm
Functions	Wire insulation stripping; half-strip with residue retention or full stripping
Working-principle	No power required, purely pneumatic-driven, fast and eco-friendly
Price	FOB - confirmed at quotation
Lead time	Confirmed at quotation

Key Features

- 2. Precise positioning with extremely high stripping accuracy.
- 3. The stripping length, cutting depth, and half/full stripping modes are all adjusted via calibrated knobs. No tool change required.
- 4. Adopts a 90-degree V-shaped blade design for excellent versatility; no blade replacement is required when switching wire sizes.
- 5. Compact size, weighing only 2 kg, easy to move, and operable anywhere with an air supply.
- 2.Production Scale: 2,500+ Units/Month capacity (500+ Auto-lines, 1000+ Semi-auto).No project delays. Mass production ready.
- 3.Rapid R&D: 3-7 Days Prototyping for custom tooling based on your unique CAD/3D drawings.Unmatched flexibility.

Commercial & Delivery

Certification	CE-certified machinery, ISO9001 factory
Quality	100% run-in tested before shipment; test video on request
Warranty	12 months standard; spare parts support
Payment	T/T 30% deposit, 70% before shipment
Packing	Export-grade wooden case / carton, QC photos before packing
Shipping	Sea, air or express - tracking provided