

TURINGNEX

Dongguan Turing Automation Technology Co., Ltd.

www.turingnex.com | Factory direct from Dongguan, China

TR-303KL TR-303KL Bilateral Pull Tape Wrapping Machine - Product Datasheet

Specifications	
Power	AC220V/50HZ,
Operating-mode	Touch Screen
Power-supply	AC220V/DC24V
Warranty	1year
Wire-diameter	φ3mm-25mm
Price	FOB - confirmed at quotation
Lead time	Confirmed at quotation
Key Features	
-	Winding length: 1050mm (longer and shorter can be customized)
-	Packing tape density: can be adjusted by the machine set parameters.
-	Hole size of the tape: machine with φ38 (other sizes φ32, φ76) (need to inform in advance)
-	Rotation speed of main machine (rpm): 200-1400 rpm adjustable
-	Applicable tape: PVC, cloth velvet, cloth-based tape, high temperature tape, mica tape, ceramic tape
-	Voltage: AC220V/DC24V 50/60HZ 110V optional
Commercial & Delivery	
Certification	CE-certified machinery, ISO9001 factory
Quality	100% run-in tested before shipment; test video on request
Warranty	12 months standard; spare parts support
Payment	T/T 30% deposit, 70% before shipment
Packing	Export-grade wooden case / carton, QC photos before packing
Shipping	Sea, air or express - tracking provided