

TURINGNEX

Dongguan Turing Automation Technology Co., Ltd.

www.turingnex.com | Factory direct from Dongguan, China

TR-308 TR-308 New Energy Continuous Tape Wrapping Machine - Product D Specifications

Power	AC220V/50HZ, 300W
Application	Tape Wrapping Machine
Feature	Stable Performance
Function	Automatic Tape Winding Machine
Warranty	1year
Equipment-name	TR-308 New Energy Tape Wrapping Machine
Compressed-air	0.5MPa
Production-capacity	360 pcs/hour
Control-method	Full digital control
Processing-specifications	Square: 15*20mm (max) Round: 20mm diameter (max)
Max.-processing-length	limitless
Min.-processing-length	130mm
Main-configuration	5-30mm
Adhesive-tape-overlap-accuracy	Deviation -0.5mm
Operating-temperature-range	5-40 degC ambient temperature
Operating-humidity-range	30%-80%RH No condensation
Price	FOB - confirmed at quotation
Lead time	Confirmed at quotation

Key Features

- Output up to 360 pcs per hour, greatly replacing manual work and boosting productivity.
- Servo synchronous moving system ensures wrinkle-free taping with overlapping tolerance <=0.5mm.
- Firmly locks workpieces on both ends to prevent shifting and avoid scratches on busbar surface.
- Built-in self-diagnosis function for faults; operators can get proficient within 15-minute training.
- Processes square & round workpieces, fits 5-30mm tape width; unlimited max processing length.
- Square: 15*20mm (max) Round: 20mm diameter (max)

Commercial & Delivery

Certification	CE-certified machinery, ISO9001 factory
Quality	100% run-in tested before shipment; test video on request
Warranty	12 months standard; spare parts support
Payment	T/T 30% deposit, 70% before shipment
Packing	Export-grade wooden case / carton, QC photos before packing
Shipping	Sea, air or express - tracking provided

Note: specifications are indicative and confirmed with your order. Custom configurations available.
Datasheet generated 2026-09-16 - Turingnex Sales Engineering