

TR-881 Stator Nylon Tie Machine - Product Datasheet

Specifications	
Power	Single-phase 220V
Application	Automatic nylon cable tie machine
Feature	Stable Performance
Warranty	1year
Contact	Coco 0086-18666170785
Power-supply	Single-phase 220V Voltage range -10%
Compressed-air	0.55 -0.5Mpa Ties specifications 2.5x100mm
Work-system	Continuous operation 24 hours a day
Operating-temperature	0-60? Operating humidity 60-95%RH
Wire-harness-diameter	1-18mm Tie head reserved length 0.5-3mm
Failure-rate	<=1? Troubleshooting time <=1s
Tie-tightness-ratio	After the workpiece tie, the tie does not slide, adjustable tightness
Tray-holds-ties-at-a-time	<=600 pieces Tightening force range 2-8kg
Price	FOB - confirmed at quotation
Lead time	Confirmed at quotation
Key Features	
-	After the workpiece tie, the tie does not slide, adjustable tightness
-	Widely used in a variety of stator, wire harness, electronic connecting wire, home appliances and other industries
-	This equipment can realize the functions of automatic discharging, feeding, coiling, tightening and cutting of d
-	1?Put the disorderly tie into the automatic discharging device, realize the tie through the pipeline to the gun h
-	2, artificial foot pedal to start the foot pedal, to achieve automatic feeding, tape, tightening, cutting and collecti
-	3?Shear the line after the wire tie head to stay tail, minimum 0.5 mm, maximum adjustable tie all the remainin
Commercial & Delivery	
Certification	CE-certified machinery, ISO9001 factory
Quality	100% run-in tested before shipment; test video on request
Warranty	12 months standard; spare parts support
Payment	T/T 30% deposit, 70% before shipment
Packing	Export-grade wooden case / carton, QC photos before packing
Shipping	Sea, air or express - tracking provided