

TURINGNEX

Dongguan Turing Automation Technology Co., Ltd.

www.turingnex.com | Factory direct from Dongguan, China

TR-889 Semi Automatic Handheld Nylon Cable Tie Machine Cable Ty Specifications

Power	AC220V/50HZ,
Application	Automatic nylon cable tie machine
Feature	Stable Performance
Warranty	1year
Contact	Coco 0086-18666170785
Power-supply	Handheld device AC 220V; gun head DC 24V
Size	Main body: L 680 * W 660 * H 650 mm
Weights	Equipment: 130kg; Gun head: 1kg
Pneumatic	5 - 6Kg/cm2 Ties specifications 2.5X80mm Straight Tail Tie for Machine Use
Min.-strapping-diameter	Ø1mm Max. Binding Diameter Ø10mm
Number-of-ties-to-be-placed-on-the-vibration-plate-at-one-time	100
Individual-tie-wrap-efficiency	1S/Pcs
Price	FOB - confirmed at quotation
Lead time	Confirmed at quotation
Key Features	
-	Handheld device AC 220V; gun head DC 24V
-	2.5X80mm Straight Tail Tie for Machine Use
-	Number of ties to be placed on the vibration plate at one time
-	Technical Requirements andFunctionalCharacteristics ofHandheld Machines
-	1. Put the disorderly loose material tie into the vibration disc randomly, the tie will be transferred to the gun head
-	2.it can be triggered by pressing the trigger (by foot pedal or customisedphotoelectric sensors after the installation)
Commercial & Delivery	
Certification	CE-certified machinery, ISO9001 factory
Quality	100% run-in tested before shipment; test video on request
Warranty	12 months standard; spare parts support
Payment	T/T 30% deposit, 70% before shipment
Packing	Export-grade wooden case / carton, QC photos before packing
Shipping	Sea, air or express - tracking provided

Note: specifications are indicative and confirmed with your order. Custom configurations available.
Datasheet generated 2026-09-16 - Turingnex Sales Engineering