

TR-A15 TR-A15 Fully Automatic Single-Wire Double-End Terminal Machine - Specifications

Power	AC220V, Single Phase 4A, approximately 1kW
Dimensions-&-weight:	1060x600x1380mm, 390kg
Applicable-wire-gauge	AWG32#~AWG18#
Crimping-capacity	1.5T
Contact	Coco : +86 18666170785
Price	FOB - confirmed at quotation
Lead time	Confirmed at quotation
Key Features	
-	Dimensions & Weight: 1060x600x1380mm, 390kg
-	Air Pressure: 0.4~0.8MPa (Clean and Dry Air Source)
-	Working Air Pressure: 0.6MPa (Air Source Requires Drying and Filtration)
-	Detection Device: Wire presence/absence, wire overload, wire joint, poor stripping, poor die stamping
-	Brand Components: Taiwan HIWIN Linear Guides, Taiwan AIRTAC Cylinder Solenoid Valves, LE
-	1.Stripping Length Adjustment Method: Adjusted by computer touch control, enabling quick chan
Commercial & Delivery	
Certification	CE-certified machinery, ISO9001 factory
Quality	100% run-in tested before shipment; test video on request
Warranty	12 months standard; spare parts support
Payment	T/T 30% deposit, 70% before shipment
Packing	Export-grade wooden case / carton, QC photos before packing
Shipping	Sea, air or express - tracking provided