

TR-CG02 TR-CG02 Auto 2 Heads Terminal Crimping Insert Heat Shrink Tube Specifications

Power	Single phase AC200V~242V 50/60Hz 10A
Application	Wires are cut, stripped at one end, stripped at bo
Feature	Stable Performance
Warranty	1year
Contact	Coco : +86 18666170785
Price	FOB - confirmed at quotation
Lead time	Confirmed at quotation
Key Features	- capacity?Wire length 80-150mm: approx. 1000 pcs/hour. Special wire: approx. 800 pcs/hour.
	- Cutting accuracy?Line length below 100mm Error 0.2+(line length x 0.002) Line length above 100
	- Processing length?Leave rubber in the middle 66mm~99999mm
	- Strip length?Front end 0.5~8.0mm; Rear end 0.1~10.0mm
	- Depth of cut?Max. adjustment 5.50mm, resolution 0.01mm
	- sensor?Low air pressure, wire presence, abnormal pressure, abnormal wire entry.
Commercial & Delivery	
Certification	CE-certified machinery, ISO9001 factory
Quality	100% run-in tested before shipment; test video on request
Warranty	12 months standard; spare parts support
Payment	T/T 30% deposit, 70% before shipment
Packing	Export-grade wooden case / carton, QC photos before packing
Shipping	Sea, air or express - tracking provided