

TURINGNEX

Dongguan Turing Automation Technology Co., Ltd.

www.turingnex.com | Factory direct from Dongguan, China

TR-DW301 Specifications

TR-DW301 Three-in-One Terminal Crimping & Heat-Shrink Tubing Machine

Power	AC220V 50/60Hz 20A
Application	wire cutting, stripping, terminal crimping
Compressed-air	0.5 MPa
Contact	Coco : +86 18666170785
Equipment-name	TR-DW301 3-in-1 Terminal Crimping & Heat-Shrink Tubing Machine
Power-supply	Single-phase AC200V~242V 50/60Hz 10A
Efficiency	Approx. 800 pieces/hour for wire length 80-150mm
Processing-length	Intermediate insulation retention: 76mm~99999mm
Stripping-length	Front end: 0.5~8.0mm; Rear end: 0.1~10.0mm
Cutter-depth	Max adjustment: 5.50mm, Resolution: 0.01mm
Size-&-weight	W 800 *D2600*H1800 mm?approx. 900KG
Detection-devices	Low air pressure, wire presence/absence, crimping abnormality, wire feeding abnormality
Wire-gauge-range	AWG22#~16#
Price	FOB - confirmed at quotation
Lead time	Confirmed at quotation
Key Features	- 2.The main unit is equipped with a built-in 4-wheel synchronous wire feeder to maintain constant wire tension - 3.Controlled by the main unit's motion control card, with Chinese/English touchscreen for parameter setting, f - 4.Compatible with horizontal-feed and straight-feed OTP terminal dies. - 5.Energy-saving, space-saving, and environmentally friendly equipment. - Mode 1: One wire is heat-shrunk with tubing, the other is not, then combined crimping, followed by heat-shrin - Mode 2: Two wires are individually heat-shrunk with tubing, then combined crimping and heat-shrinking with a
Commercial & Delivery	
Certification	CE-certified machinery, ISO9001 factory
Quality	100% run-in tested before shipment; test video on request
Warranty	12 months standard; spare parts support
Payment	T/T 30% deposit, 70% before shipment
Packing	Export-grade wooden case / carton, QC photos before packing
Shipping	Sea, air or express - tracking provided