

TURINGNEX

Dongguan Turing Automation Technology Co., Ltd.

www.turingnex.com | Factory direct from Dongguan, China

TR-HT01 TR-HT01 Full-Automatic Double-Head Heat Shrink Tubing & Sleeve Specifications

Power	220V 50/60Hz, 2kW
Application	wire cutting, stripping, terminal crimping
Stripping-length	1mm~7mm
Working-air-pressure:	0.6MPa(clean filtered air source)
Contact	Coco : +86 18666170785
Price	FOB - confirmed at quotation
Lead time	Confirmed at quotation
Key Features	
-	Dimensions & Weight: 2000x800x800mm, 480kg
-	Working Air Pressure: 0.6MPa (clean filtered air source)
-	Applicable Wire Diameter: 1mm~5mm (1007 wire, PVC wire, Teflon wire, braided silicone wire, a
-	Special Functions: Single-head terminal crimping, double-head terminal crimping, single-head sir
-	Auxiliary Functions: Pre-feeding device, terminal, waste paper winding device
Commercial & Delivery	
Certification	CE-certified machinery, ISO9001 factory
Quality	100% run-in tested before shipment; test video on request
Warranty	12 months standard; spare parts support
Payment	T/T 30% deposit, 70% before shipment
Packing	Export-grade wooden case / carton, QC photos before packing
Shipping	Sea, air or express - tracking provided