

TR-HT03 TR-HT03 Multi-core Wire Automatic Stripping And Terminal Crimping Machine Specifications

Power	AC220V/50HZ,
Application	Double end Terminal Machine
Feature	Stable Performance
Warranty	1year
Control	Servo and Step motor
Contact	Lily 0086-13715588365
Equipment-name	TR-HT03 Multi-core Wire Automatic Wire Stripping Terminal Crimping Machine
Power-supply	AC220V 50/60Hz single phase,700W
Operation-mode	Manual, single cycle, fully automatic
Size-&-weight	650x850x1350mm,150kg
Working-efficiency	650 pcs/H
Wire-specification	Min. outer sheath stripping length: 28mm, Wire gauge: 28AWG~18AWG, Wire diameter: ~0.8~2.5mm, Max. 1
Air-pressure	5kg
Pressure	Conventional 1.5T stamping machine
Detection-device	With or without wire, wire knots, abnormal stripping. Poor stamping die, terminal with or without, terminal over
Tool-material	Tungsten steel / high speed steel
Price	FOB - confirmed at quotation
Lead time	Confirmed at quotation
Key Features	
-	Specially designed for multi~core sheathed wires, it integrates wire trimming, stripping and terminal crimping.
-	The cassette mold and stripping unit are independent of each other, making cassette mold replacement quick
-	Adjustable stripping depth to satisfy diverse processing requirements; capable of processing wires with up to
-	Equipped with self~developed 1.5T steel~plate silent terminal machine for low~noise operation, with 1.5T crim
-	Wecon bilingual Chinese~English touch~screen for fool~proof operation, low learning threshold for operators.
-	Adopts well~known brand accessories including HIWIN linear guides & lead screws, Airtac solenoid valves and
Commercial & Delivery	
Certification	CE-certified machinery, ISO9001 factory
Quality	100% run-in tested before shipment; test video on request
Warranty	12 months standard; spare parts support
Payment	T/T 30% deposit, 70% before shipment
Packing	Export-grade wooden case / carton, QC photos before packing
Shipping	Sea, air or express - tracking provided