

TURINGNEX

Dongguan Turing Automation Technology Co., Ltd.

www.turingnex.com | Factory direct from Dongguan, China

TR-HY03 Fully Automatic Double-Line Combined Press Three-Penetration Heat Shrinkable Tube Feeding Machine Specifications

Power	AC220V, Single-phase 8A
Control	Servo and Step motor
Dimensions	1100+3000/2*H1650mm
Display-language	Chinese/English
Wire-diameter	1.6mm~3.6mm (Customizable for sizes beyond this range)
Processing-length	Middle Reserved Length 80-999mm
Stripping-length	1-14mm Ideal Range
Cutting-error	Correctable -0.2mm
Air-supply	0.5MPa Clean Dry Gas
Tube-sheath-detection	Detectable/Undetectable (Optical Fiber)
Terminal-detection	Detectable/Undetectable (Optical Fiber)
Price	FOB - confirmed at quotation
Lead time	Standard models in stock; customised machines 7-15 days

Key Features

- Double-line combined pressing with three-penetration heat-shrinkable tube feeding
- Wire feeding, cutting and stripping in one continuous cycle
- Servo and stepper motor drive with optical-fiber detection

Commercial & Delivery

Certification	CE-certified machinery, ISO9001 factory
Quality	100% run-in tested before shipment; test video on request
Warranty	12 months standard; spare parts support
Payment	T/T 30% deposit, 70% before shipment
Packing	Export-grade wooden case / carton, QC photos before packing
Shipping	Sea, air or express - tracking provided