

TR-JL05 TR-JL05 Single Rivet Caster Brake Assembly Machine - Product Data Sheet

Specifications	
Speed	15-20pcs/min
Contact	Coco 0086-18666170785
Plc-brand	Xinjie
Price	FOB - confirmed at quotation
Lead time	Confirmed at quotation
Key Features	
-	Work environment : 0.5-0.75Mpa (dry air)
-	Riveting pressure : 0.57 t (capable of riveting a single semi-hollow core rivet up to a maximum diameter of 10mm)
-	1. Intelligent system: Exclusive R&D system with simple interface for easy operation. Fault automatic diagnosis and alarm.
-	2. Controllable Parameters: All key parameters of the equipment release station can be quickly modified through the touch screen.
-	3. Intelligent workstation: a workstation can be closed or opened individually through the touch screen.
-	4. Comfortable operation: The height of the manual position of the machine is designed according to the ergonomic principle.
Commercial & Delivery	
Certification	CE-certified machinery, ISO9001 factory
Quality	100% run-in tested before shipment; test video on request
Warranty	12 months standard; spare parts support
Payment	T/T 30% deposit, 70% before shipment
Packing	Export-grade wooden case / carton, QC photos before packing
Shipping	Sea, air or express - tracking provided