

TR-KL02 Automatic Coil Tape Wrapping Machine - Product Datasheet

Power-supply	220V/50HZ 550W
Dimensions-weight	670x390x480mm, 30kg
Outer-diameter-of-tape-roll	Max ?120mm
Inner-diameter-of-tape-roll	?76mm
Operating-air-pressure	4KG/cm2
Production-efficiency	1.5~5 S (Customized, subject to equipment performance)
Tape-width	5~20mm (Customized, subject to production contract)
Cutting-length	20~90mm (Customized, subject to production contract)
Price	FOB - confirmed at quotation
Lead time	Standard models in stock; customised machines 7-15 days, confirmed at quotation
Key Features	

- Suitable for internal tape wrapping of electronic coils, stator windings and inductor coils
- Compatible with crepe tape, Mylar tape, barrier tape and high-temperature tape
- Tape wrapping cycle 1.5 seconds with adjustable turns and length
- Automatic alert for tape shortage for quick replacement

Commercial & Delivery

Certification	CE-certified machinery, ISO9001 factory
Quality	100% run-in tested before shipment; test video on request
Warranty	12 months standard; spare parts support
Payment	T/T 30% deposit, 70% before shipment
Packing	Export-grade wooden case / carton, QC photos before packing
Shipping	Sea, air or express - tracking provided