

# TURINGNEX

Dongguan Turing Automation Technology Co., Ltd.

www.turingnex.com | Factory direct from Dongguan, China

## TR-PX1 Specifications

|                                |                                                                                                               |
|--------------------------------|---------------------------------------------------------------------------------------------------------------|
| Power                          | AC220V/50HZ,                                                                                                  |
| Application                    | Double end Terminal Machine                                                                                   |
| Feature                        | Stable Performance                                                                                            |
| Warranty                       | 1year                                                                                                         |
| Control                        | Servo and Step motor                                                                                          |
| Contact                        | Coco 0086-18666170785                                                                                         |
| Model-no.                      | TR-PX1                                                                                                        |
| Power-supply                   | AC220V 50/60HZ                                                                                                |
| Funtion                        | Wire cutting, single end peeling.double end peeling, single endpressing, double end pressing.single end three |
| Capacity                       | 800 pcs/hour for cable 12P (depending on wire)                                                                |
| Processing-model               | AWG#30-AWg #18 for cable type , 26#-18# for electric wire                                                     |
| Cutting-length                 | 45mm-1000mm(change the minimum cutting length according to the peeling size)                                  |
| Cutting-tolerance              | Variation range: 1mm+ cut length lessthan 0.1%                                                                |
| Front-and-end-stripping-length | 0mm-8mm                                                                                                       |
| Max-wire-width                 | 28mm                                                                                                          |
| Air-pressure                   | 0.4-0.6 MPa clean and dry air                                                                                 |
| Machine-size                   | 1920*1520*1750mm                                                                                              |
| Weight                         | 600kg                                                                                                         |
| Special-function               | Two or more lines can be processed at the same time (including two Electronic wires can simultaneously pro    |
| Price                          | FOB - confirmed at quotation                                                                                  |
| Lead time                      | Confirmed at quotation                                                                                        |
| Commercial & Delivery          |                                                                                                               |
| Certification                  | CE-certified machinery, ISO9001 factory                                                                       |
| Quality                        | 100% run-in tested before shipment; test video on request                                                     |
| Warranty                       | 12 months standard; spare parts support                                                                       |
| Payment                        | T/T 30% deposit, 70% before shipment                                                                          |
| Packing                        | Export-grade wooden case / carton, QC photos before packing                                                   |
| Shipping                       | Sea, air or express - tracking provided                                                                       |

Note: specifications are indicative and confirmed with your order. Custom configurations available.  
Datasheet generated 2026-09-16 - Turingnex Sales Engineering